

# PUS-V200C

Camera ePTZ 4K per conferenza



Supporto  
regolabile

30° Verticale

Microfono  
integrato

Distanza 8 metri



FC CE RoHS ISO







# Plug to Play Easy for AV Application

Support USB3.0, HDMI Simultaneous Video Output

Voice  Video  Power Supply   
Communication function



## Rubik's Cube Appearance

More Stable Quality & More Reliable

It can be configured with a vertical angle of 30°  
Adjustable bracket



■ Desktop ■ PC/Laptop ■ Touchboard ■ Tripod



## High-quality High-fidelity Audio Input

8 meters long distance, 360° Voice pickup

Automatic Gain Control   
Deep Echo Cancellation   
Dynamic Noise Suppression



## Super Compatible

Super Compatible All Video Application & Conferencing  
System Apk or Software

Windows  IOS  Android  Linux



# Specifications

|               |                      |   |
|---------------|----------------------|---|
| <b>Camera</b> | Video System         | Sony 1/2.5" CMOS, Effective Pixel 4K@3820*2160  |
|               | Video Output Format  | 4K@30fps;<br>1920*1080P@60fps/50/30/25fps;<br>1080I@60fps/50fps;<br>720p@60fps/50fps; 320*480 |
|               | Lens 1               | F=3.5mm FOV 110°  |
|               | Lens 2 (Default)     | F=2.8mm FOV 130°  |
|               | Auto Focus           | Support   |
|               | Min Illumination     | 0.02Lux @ F1.8, AGC ON)   |
|               | Shutter              | 1/30s ~ 1/10000s  |
|               | White Balance        | Auto / Indoor /Outdoor/ ONE PUSH, Manual  |
|               | Camera Brackets      | Brackets with Damper Support ± 30° adjustment   |
|               | Digital Noise Reduce | 2D, 3D  |
|               | BLC                  | Support   |
|               | WDR ON/OFF           | Support   |

|                       |                     |          |
|-----------------------|---------------------|----------|
| <b>Audio Function</b> | Built-in Microphone | YES      |
|                       | Audio Transmission  | USB 3.0  |
|                       | Voice Pickup Range  | 8 Meters |

|                       |              |  |
|-----------------------|--------------|--|
| <b>HDMI Interface</b> | Video Output | 4K@30fps;<br>1920*1080P@60fps/50/30/25fps;<br>1080I@60fps/50fps;<br>720p@60fps/50fps; 320*480  |
|                       | Encoding     | H.265 / H.264 / MJPEG  |
|                       | Audio Output | N/A  |
|                       | ePTZ         | Support, 4X Digital Zoom @1080P  |
|                       | Interface    | USB3.0 Type B Female<br>(Compatible with all interfaces below USB3.0, support video, control, power supply, audio input and output)<br><br>HDMI 2.0<br>(Compatible with HDMI 2.0, 1.4, 1.3A, 1.3 and other interfaces, only supports video transmission) |

|                     |                     |   |
|---------------------|---------------------|---|
| <b>USB Function</b> | Video Output        | 4K@30fps;<br>1920*1080P@60fps/50/30/25fps;<br>1080I@60fps/50fps;<br>720p@60fps/50fps; 320*480 |
|                     | Encoding            | H.265 / H.264 / MJPEG   |
|                     | UVC Protocol        | Support   |
|                     | Video Communication | UVC1.0 - UVC1.5   |

|                |                       |                   |
|----------------|-----------------------|-------------------|
| <b>Generic</b> | Input Voltage         | 5V(USB 3.0)       |
|                | Operation Temperature | -10°C ~+50°C (14) |
|                | Storage Temperature   | -40°C ~ 60°C      |
|                | Power Consumption     | TBD               |
|                | MTBF                  | 50000hours        |

**Accessories:** 1\* PUS-V200C Camera; 1\* Remote Control 1\* User Manual; 1\* USB3.0 Cable

## Products Picture



**Shenzhen PUAS Industrial Co., Ltd**  
2/F, C/Building, Huawang Industrial Park, Longhua New District,  
Shenzhen, GD, China

+86 0755-88361222 | sales01@szpuas.net

Copyright © 2019 Shenzhen PUAS industrial co., LTD. All rights reserved.  
It's not allowed to use this pictures and logos in any form include reproduce and modify without the PUAS's permission

